



## Product Specification &

# SAFETY DATA SHEET

CHIP / EC FORMAT 91/155/EEC AMD 93/112/EC AMD 2001/58/EC



## B128

# FABRIC SEAL

### SECTION 1: IDENTIFICATION OF THE PREPARATION AND COMPANY

**Product Name:** FABRIC SEAL

**Product Code:** B128

**Manufacturer:** Prochem Europe Ltd., Oakcroft Road, Chessington, Surrey KT9 1RH, UK. Telephone No: 020 8974 1515 (UK) +44 20 8974 1515 (EC) Chemical Product Manager E, H & S

**Emergency Action:** In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department, who may seek advice from the **UK National Poisons Information Service**, where our full product details are held.

#### Product Description & Directions For Use:

A solvent based, chlorine free, fluorochemical upholstery fabric protector and stain repellent designed to impart oil, water, soil and stain resistance to water sensitive fine upholstery fabrics.

**Always refer to Safety Data Sheet before use.**

Fabric to be treated should be clean and dry. Previously wet cleaned fabric must be extraction rinsed, towelled and as dry as possible before application. B128 may be applied directly after dry cleaning processes. Always pre-test fabric for colour fastness and texture change in an inconspicuous area before proceeding.

Fabric Seal is ready-to-use. Do not dilute with water or solvent. Ensure adequate ventilation, no smoking and prohibit people and pets from application area.

**Always wear an approved organic solvent cartridge mask, safety glasses and gloves when applying this product.**

Apply lightly and evenly to fabric with approved Prochem fabric protector applicator. Do not use trigger sprayer or fine mist atomised spray. Do not over-apply or saturate fabric. Recommended coverage is approx. 80 to 100 square metres of fabric per 5 litres or 250ml per seat. Allow fabric to dry completely (several hours or overnight) before re-use.

**DO NOT APPLY FABRIC SEAL TO CARPETS.**

### SECTION 2: COMPOSITION / INFORMATION ON INGREDIENTS

SUBSTANCE	RISK (See Section 16)	EINECS NO.	CAS NO.	% W/W (EC RANGE)
Aliphatic hydrocarbon	Xn R65 R66 R53	649-275-00-4	64741-65-7	More than 30%
Fluorocarbon resin	None assigned	None	None	5 to 15%

### SECTION 3: HAZARDS IDENTIFICATION

**Classification:** Harmful: May cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. May cause long-term adverse effects in the aquatic environment.

**Eye Contact:** Contact with liquid or high concentration of vapour may cause slight eye irritation.

**Skin Contact:** Prolonged or repeated contact will dry the skin and cause irritation and possible dermatitis.

**Inhalation:** Excessive exposure above recommended level may cause headache and breathing irritation. May be harmful or fatal if aspirated into lungs.

**Ingestion:** Low oral toxicity. May be harmful or fatal if swallowed and aspirated into lungs.

**Environment:** Not inherently biodegradable. May bioaccumulate. See Ecological Information for further details.

### SECTION 4: FIRST AID MEASURES

**Eye Contact:** Flush immediately with water for 15 minutes holding eyelids apart, then seek medical attention.

**Skin Contact:** Wash skin with soap and water. Use shower if necessary. Seek medical attention if irritation persists.

**Inhalation:** Remove from exposure and move to fresh air at once. Keep warm and at rest. If breathing is difficult, obtain immediate medical assistance and give oxygen. Perform artificial respiration if breathing has stopped.

**Ingestion:** If swallowed, **DO NOT INDUCE VOMITING** unless directed to do so by medical personnel. Seek medical advice immediately and show the container or label.

### SECTION 5: FIRE FIGHTING MEASURES

**Extinguishing Media:** Use water, carbon dioxide, dry powder extinguisher, foam, or water spray to keep containers cool.

**Fire/Explosion Hazards:** Vapours heavier than air. Flash point 60°C. Explosive limits for hydrocarbon in air 0.6% - 6% v/v.

**Decomposition Products:** Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids and other unidentified thermal decomposition products from this product or its packaging.

**Special Protective Equipment:** Self contained breathing apparatus and full protective clothing.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

**Personal Protection:** Avoid contact with liquid. Ventilate area and remove all sources of ignition. Wear protective clothing, solvent resistant rubber gloves, chemical splash goggles. Under severe conditions use respiratory protection or breathing apparatus.

**Containment and Disposal:** Prevent liquid from entering drains or water courses. Advise water authority if large amount of solvent enters drain or water course. Contain and absorb with sand, earth or vermiculite. Do not use combustible materials such as sawdust. Transfer to suitable container for disposal by licensed contractor at legal waste disposal site. Wash area of spillage with plenty of water and detergent.

### SECTION 7: HANDLING AND STORAGE

**Handling Precautions:** Wear solvent resistant rubber gloves and safety glasses when handling liquid. Do not breathe vapour/spray. Ensure adequate ventilation and eliminate all ignition sources - no smoking. Always wear an approved organic solvent cartridge mask when applying this product.

**Storage Precautions:** Store in a cool dry ventilated area away from any source of heat, ignition, static electricity or direct sunlight. Maximum recommended storage temperature is 30°C. Keep away from strong acids, alkalis and oxidising agents. Keep out of reach of children. Keep in original container.

## **SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Exposure Limits:** Recommended Workplace exposure limit OEL-LTEL 150ppm.

**Environmental Controls:** For additional guidance, contact ENVIROWISE at [www.envirowise.gov.uk](http://www.envirowise.gov.uk) or telephone 0800 585794

**Eye Protection:** Side shield safety glasses or goggles are recommended when handling or during spraying.

**Protective Clothing:** Standard work clothing and solvent resistant NBR rubber gloves. Protective gloves should be inspected for wear before use and replaced regularly in accordance with the manufacturers specifications.

**Respiratory Protection:** For situations where recommended exposure limits may be exceeded or where there is a risk of inhalation of fine spray mists, an approved organic solvent twin cartridge face mask with appropriate filter (e.g. 3M 6000 Series half-mask respirator) should be used.

**Ventilation:** Ensure good air circulation and ventilation in enclosed areas. Use forced air fans if necessary.

**Hygiene:** Wash hands and clothing after use or spill. Do not eat or drink when handling solvent. DO NOT SMOKE IN WORK AREA.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance/Colour/State:** Clear colourless liquid

**Odour:** Faint aromatic solvent

**pH Concentrate:** Not applicable

**pH Diluted:** Not applicable

**Boiling Point / Range °C:** 187 to 213 @ 760mmHg

**Flash Point °C:** 60 **Method:** PM Closed cup

**Flammability Limit %:** 0.6 to 6

**Explosive Properties:** Not determined

**Oxidising Properties:** Not applicable

**Vapour Pressure:** 0.2 kPa (1.2 mmHg) @ 20°C

**Relative Density (Water = 1):** 0.761g/cm<sup>3</sup> @ 15°C

**Solubility:** Insoluble in water. Soluble in hydrocarbons

**Partition Coefficient (N-octanol / Water):** Not determined

**Viscosity:** Not determined

**Vapour Density:** 4.5

**Evaporation Rate:** 0.14 (Butyl Acetate = 1)

**% Active:** 6

**% Solids:** 4

## **SECTION 10: STABILITY AND REACTIVITY**

**Stability:** Stable

**Conditions to Avoid:** Heat, ignition sources, static build-up, direct sunlight.

**Incompatibility (Materials to Avoid):** Strong oxidising or alkaline agents.

**Hazardous Decomposition Products:** Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids and other unidentified thermal decomposition products from this product or its packaging.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

**Eye Contact:** Liquid and vapour (at higher temperatures and concentrations) may cause transient eye irritation effects.

**Skin Contact:** Prolonged exposure will cause defatting and may produce a dry, scaly and fissured dermatitis.

**Inhalation:** May be harmful or fatal if aspirated into lungs. Excessive exposure to hydrocarbon vapour at high temperatures may cause central nervous depression. Acute overexposure to inhalation of spray mist may cause lung congestion and oedema.

**Ingestion:** Low oral toxicity. Swallowing chemical may cause severe internal injury, irritation of digestive tracts, vomiting and diarrhoea followed by CNS effects. May be harmful or fatal if aspirated into lungs. Chemical pneumonia and pulmonary oedema if quantities are aspirated into lungs.

**Acute and Chronic Effects:**

**Acute Toxicity:** LD50 >2000mg/Kg (oral-rat) (Aliphatic hydrocarbon)

LD50 >2000mg/Kg (skin-rat) (Aliphatic hydrocarbon)

**Corrosivity / Irritation:** Skin, eye and respiratory

**Sensitisation:** None Known

**Repeated Dose Toxicity:** Not established

**Mutagenicity:** None

**Carcinogenicity:** None

**Teratogenicity:** None

## **SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity:** Low aquatic and mammalian toxicity. May cause long-term adverse effects in the aquatic environment.

**Mobility:** Will float on water and evaporate slowly. Dissolved material adsorbs strongly to soil and sediment and is not mobile. Product remaining on soil surface evaporates within one day.

**Persistence and Degradability:** Not inherently biodegradable. Oxidises rapidly by photochemical reactions in air. Integrated environmental half-life expected to be 10 - < 100 days. The major packaging materials of polyethylene and fibreboard are recyclable.

**Bioaccumulative Potential:** Has potential to bioaccumulate.

**Other Effects:** None known or no relevant data available for substances in this preparation.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste cleaning solvent effluent should be transferred to suitable containers and disposed of in accordance with special waste regulations (Special Waste Regulations 1996, Environment Act 1995 and Environmental Protection Act 1990). Do not allow solvent to enter drains. Empty containers should be rinsed with water then crushed and disposed of at legal waste disposal site. Contact local Environment Agency office for waste holder requirements.

## **SECTION 14: TRANSPORT INFORMATION**

**UN No:** 3295

**Classification:** Flammable Liquid

**Proper Shipping Name:** Hydrocarbons, Liquid, N.O.S (Solvent Naphtha solution)

**Packing Group:** III

**Road (ADR):** Class 3 'limited quantity'

**Sea (IMDG):** Class 3 'limited quantity'

**Air (ICAO / IATA):** Class 3

**Rail (RID):** Class 3

## **SECTION 15: REGULATORY INFORMATION**

**Classification:** Xn HARMFUL

**Risk Phrases**

R53 May cause long-term adverse effects in the aquatic environment.

R65 Harmful: May cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

**Safety Phrases**

S2 Keep out of the reach of children.

S23 Do not breathe vapour / spray.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37/39 Wear suitable gloves and eye/face protection.

S42 During spraying wear suitable respiratory equipment.

S51 Use only in well-ventilated areas.

S60 This material and its container must be disposed of as hazardous waste.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

The information given has been compiled with reference to the **CHEMICALS (HAZARD INFORMATION AND PACKAGING FOR SUPPLY) REGULATIONS (CHIP 3) 2002** (as amended), the **CONTROL OF SUBSTANCES HAZARDOUS TO HEALTH REGULATIONS (COSHH) 2002** (as amended) and the **MANAGEMENTS OF HEALTH AND SAFETY AT WORK REGULATIONS 1999** (as amended).

This safety data sheet does not constitute the users own assessment of workplace risk as required by other health and safety regulations.

## **SECTION 16: OTHER INFORMATION**

**Risk Phrases:** R53 May cause long-term adverse effects in the aquatic environment. R65 Harmful: May cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking.

For additional information on safety, training and use of this product, contact the supplier. This product is intended for professional use only. The information given is intended to be of assistance to users but is without guarantee. Variations can occur in application and users are advised to conduct their own tests. Suggestions for use neither give nor imply any guarantee as to the intended use.

**Revisions:** Replaces SDS B128 Issue / Revision Date 01/11/03  
Revised Sections: 1, 2, 3, 4, 6, 7, 8, 9, 11, 12, 14, 15, 16