



M176 FULL POWER GRAFFITI REMOVER

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

PRODUCT CODE: M176
PRODUCT NAME: FULL POWER GRAFFITI REMOVER
MANUFACTURER: Selden Research Limited
Staden Lane
Ashbourne Road
Buxton
Derbyshire
SK17 9RZ

TELEPHONE: 01298 26226
FAX: 01298 26540
EMAIL: safety@selden.co.uk

2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME CAS No.:	EINECS Nr.:	CLASSIFICATION	CONTENT
ALCOHOL ETHOXYLATE		Xi;R38,R41.	5-10 %
ETHOXYLATED FATTY AMINE 25307-17-9	246-807-3	Xn;R22. C;R34. N;R50.	0-1 %
PROPYLENE CARBONATE 108-32-7	203-572-1	Xi;R36	10-30 %

The full text for all R-Phrases are displayed in Section 16

3. HAZARDS IDENTIFICATION

R36 Irritating to eyes.

4. FIRST AID MEASURES

INHALATION: Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION: Remove victim immediately from source of exposure. DO NOT INDUCE VOMITING!, Rinse mouth thoroughly. Drink plenty of water. Get medical attention.

SKIN: Remove affected person from source of contamination. Remove contaminated clothing. Rinse with water. Get medical attention if any discomfort continues.

EYES: Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials. Use: Dry chemicals, sand, dolomite etc. Foam. Water spray.

SPECIAL FIRE FIGHTING PROCEDURES: Use water to keep fire exposed containers cool and disperse vapours.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS: Wear necessary protective equipment. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS: Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS: Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:





M176 FULL POWER GRAFFITI REMOVER

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Liquid
COLOUR:	colourless
ODOUR:	Characteristic, Solvent.
BOILING POINT (°C):	>100
DENSITY/SPECIFIC GRAVITY(g/ml)	1.1
pH-VALUE, CONC. SOLUTION:	Not applicable
VISCOSITY:	Typically 2500 cps 20
SOLUBILITY:	Miscible with water.
FLASH POINT (°C):	>100 CC (Closed

10. STABILITY AND REACTIVITY

STABILITY:	Stable under normal temperature conditions.
HAZARDOUS COMPOSITION PRODUCTS:	Fire or high temperatures create:, Toxic gases/vapours/fumes of:, Carbon dioxide (CO ₂). Carbon monoxide (CO).

11. TOXICOLOGY INFORMATION

INGESTION:	Gastrointestinal symptoms, including upset stomach. Diarrhoea.
SKIN CONTACT:	Liquid may irritate skin. Contains ingredients which may penetrate the skin.
EYE CONTACT:	Irritating to eyes.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:	Not classed as Hazardous to the Environment but release to the environment should be avoided.
--------------	---

13. DISPOSAL CONSIDERATIONS

DISPOSABLE METHODS:	Dispose of waste and residues in accordance with local authority requirements.
---------------------	--

14. TRANSPORT INFORMATION

ROAD TRANSPORT NOTES:	Not Classified
SEA TRANSPORT NOTES:	Not Classified.
AIR TRANSPORT NOTES:	Not Classified.

15. REGULATORY INFORMATION

LABEL FOR SUPPLY:



RISK PHRASES:	R36 Irritating to eyes.
SAFETY PHRASES:	S23 Do not breathe vapour/spray. S25 Avoid contact with eyes. S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S51 Use only in well-ventilated areas. S37/39 Wear suitable gloves and eye/face protection.
STATUTORY INSTRUMENTS:	Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.
APPROVED CODE OF PRACTICE:	Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES:	Workplace Exposure Limits EH40. CHIP for everyone HSG(108).



M176 FULL POWER GRAFFITI REMOVER

16. OTHER INFORMATION

USER NOTES:

REVISION DATE:

REV. NO./REPL. SDS GENERATED:

R-PHRASES (Full Text):

The following risk phrases relate to the raw materials in the product and not the product itself:-
20/06/2006

2

R36 Irritating to eyes. | R22 Harmful if swallowed., R34 Causes burns., R50 Very toxic to aquatic organisms. | R38 Irritating to skin., R41 Risk of serious damage to eyes. |