

K184 : SILICONE - TANGERINE

NEW TRIM TANGERINE



| | |
|----------------------|------|
| SILICONE - TANGERINE | K184 |
|----------------------|------|

| | |
|-------------|---|
| | new trim tangerine |
| description | air conditioning vinyl renovator Renovates - gives a high gloss instant shine. Reodorises - unique air conditioning properties absorb stale odours. |
| application | For renovating car dashboards, vinyl and plastic trim. New Trim Tangerine will give an instant gloss finish enhancement. Can also be used on wood and metal surfaces |
| directions | Hold can as upright as possible, spray approximately 20cm from surface. Spray lightly over the surface to achieve the required level of finish. Polishing the sprayed surface with a lint free cloth will ensure a uniform finish and remove any excess. N.B. Product contains silicone fluids. DO NOT use near body shops or paint spraying areas. |

| Technical | | | | | | | | | | | | | |
|-------------|---|-------------|-------------------------------------|------------|-------------|--------|------------|---------|------|-----------|-----------|-----------|-------------------|
| | <table><tr><td>Composition</td><td>Silicone fluid, perfume and solvent</td></tr><tr><td>Appearance</td><td>Clear spray</td></tr><tr><td>Colour</td><td>Colourless</td></tr><tr><td>Density</td><td>0.61</td></tr><tr><td>Fragrance</td><td>Tangerine</td></tr><tr><td>Stability</td><td>Two years minimum</td></tr></table> | Composition | Silicone fluid, perfume and solvent | Appearance | Clear spray | Colour | Colourless | Density | 0.61 | Fragrance | Tangerine | Stability | Two years minimum |
| Composition | Silicone fluid, perfume and solvent | | | | | | | | | | | | |
| Appearance | Clear spray | | | | | | | | | | | | |
| Colour | Colourless | | | | | | | | | | | | |
| Density | 0.61 | | | | | | | | | | | | |
| Fragrance | Tangerine | | | | | | | | | | | | |
| Stability | Two years minimum | | | | | | | | | | | | |
| Storage | Pressurised container. Store out of direct sunlight. Temperature must not exceed 50oC | | | | | | | | | | | | |

| Aerosol Information | | | | | | | |
|---------------------|--|------------|-------------|----------|--------|------------|-----|
| | <table><tr><td>Propellant</td><td>Hydrocarbon</td></tr><tr><td>Pressure</td><td>48 psi</td></tr><tr><td>Spray Rate</td><td>0.9</td></tr></table> | Propellant | Hydrocarbon | Pressure | 48 psi | Spray Rate | 0.9 |
| Propellant | Hydrocarbon | | | | | | |
| Pressure | 48 psi | | | | | | |
| Spray Rate | 0.9 | | | | | | |

Product is for professional use only.